

O-LOX® posts

Posts

Rigid post system with coverplate or stainless steel fixing plate.

Variable fixing systems and post caps.

BENEFITS

- 3 different fixing systems for 1 standard post
- Possibility to choose the post cap
- Steps of 200 mm

Product detail



with coverplate



with stainless steel fixing plate

Profile

- Posts are foreseen of inserts every 200 - 400 mm
- PA clamps to support the panels are fixed to the posts with inserts M8
- Cross section post: 60 x 40 mm
- Plate thickness: 1.50 mm or 2 mm, depending on the height of the fence
- I/V 1.5 mm = 5.0 cm³
- I/V 2.0 mm = 6.19 cm³

Accessories

- Posts can be covered with post caps with or without overhang
- Flat steel cover plates (40x4mm)
- Stainless steel fixing plates of butterfly fixators
- Coverplate or fixing plates are bolted to the post with stainless steel bolts M8x40
- Corner clamps



Coating technique

Galvanised in-and outside (275 g/m² - both sides combined) and plastic coated (min. 60 micron)

Colours

Standard available in galvanised execution, in green (RAL 6005) and grey (RAL 7016).

Options

Posts can also be delivered with welded floorplates.

O-LOX® POSTS

Panel height mm	Post section mm	Post length mm	Inserts
630	60 x 40 x 1.5	1000	3
830	60 x 40 x 1.5	1300	4
1030	60 x 40 x 1.5	1500	4
1230	60 x 40 x 1.5	1700	5
1430	60 x 40 x 1.5	2000	5
1630	60 x 40 x 1.5	2200	6
1830	60 x 40 x 2	2400	6
2030	60 x 40 x 2	2600	7
2230	60 x 40 x 2	2800	7
2430	60 x 40 x 2	3000	8

Compatible products

- Nylofor 2D/2DS