

SPECIFICATION TEXT

ST-Gpod Mini Linear / Mobile, Silent and Private Work Space

Type	Gustafs Gpod with acoustic Linear outer wall surfaces.
Capacity	For 1 person, working facing the left or right wall or the backside glass. For lay outs see www.gustafs.com
Outer dimensions	Total footprint: 1420x1250 mm (wxd) Total height: 2380 mm
Inner dimensions	Floor space: 990x1220 mm (wxd) Standing height: 2010 mm
Mobility	By integrated wheels, can be rolled over 20 mm thresholds. By forklift - can be raised 100 mm from the floor. By forklift - truly self-supporting construction.
Placement	Universal placement for Centre, Wall, Left Corner and Right Corner
Weight	490 kg
Front door	Full width door 2000x1007 mm, opening 180° to full width. Magnet soft close. Sound proof glass, tempered, privacy dark tone.
Backside glass	990x1999 mm, sound proof glass, tempered, privacy dark tone.
Surfaces	All veneers are real wood veneer in architectural quality. Other veneers than the standards below on request only. Front Frame: Ash / Oak / Cherry / Walnut Back Frame: Ash / Oak / Cherry / Walnut Outside walls: Ash / Oak / Cherry / Walnut / White / Black Inside walls: Ash / Oak / Cherry / Walnut / White CPL / Black CPL Inside ceiling: Ash / Oak / Cherry / Walnut Inside flooring: Anthracite Grey
Surface treatment	Triple UV coating approved for cleaning with up to 70% alcohol products / Pigmented Triple UV coating approved for cleaning with up to 70% alcohol products. The flooring is antistatic, dirt resistant and acoustic.
Veneer Direction	Along length
Fixture system	For the wall and ceiling claddings Gustafs Capax is used, consisting of aluminium profiles gripping the full length of the sides of the panels, levelling and aligning the panels.

SPECIFICATION TEXT

ST-Gpod Mini Linear / Mobile, Silent and Private Work Space

Intelligent sensor	Measures light, air quality and motion. Connected to and automizing the lightning and ventilation, all by OCHNO Operated.		
Ventilation	Oversized airflow of 45,1 l/s (162,4 m3/h), achieved with 6 low speed whisper fans. Automatic/manual rpm control and sound proof in- and outlets.		
Air inlet	Easy access regardless the placing of the Gpod for cleaning and maintenance		
Power input	230 V, enters from left, right or the roof. This can be changed anytime.		
Sockets, output	2 x USB-C		
Lightning	2 x LED spotlights, automatic/manual control, dimmable.		
Wheels	4 pcs, diameter 125 mm, swing.		
Adjustable feet	4 pcs, adjustable from 20 – 100 mm height, access from the inside.		
Reaction to Fire	Up to A2-s1,d0 (EN 13501-1) for the inside claddings Up to B-s1,d0 (EN 13501-1) for the outside claddings All valid including the fixture system, the veneered surface and lacquer.		
Resistance to Fire	Up to K1-10/K2-10 (EN 13501-2)		
Acoustic absorption	Outside walls: Gustafs Linear	α_w 0,70-B	NRC 0,8
	Inside wall: Gustafs Nano	α_w 0,85-B	NRC 0,9
	Inside ceiling: Gustafs Stripes RP8-C20	α_w 0,65-C	NRC 0,7
	Inside flooring: Sound absorbing carpet	α_w 0,30-D	NRC 0,45
Sound proof	<p>The sound insulation of Gpod is great and they can be placed next to other workstations in the middle of an office and people working next to the pods will not be able to hear discussions taking place in them. Conversations inside Gpod can be made 100% discrete.</p> <p>We prefer not to give out the results of sound insulation measurements done to our product. At the moment, there isn't a standardized test for measuring the sound insulation of small enclosed spaces like Gpod. The sound insulation of a Gpod also varies depending on measuring sound coming out from the Gpod and sound entering the Gpod and there are no standardized tests covering this phenomenon. That is why existing acoustical ratings are not a good reflection of the experience using a Gpod. We recommend you try a Gpod in order to evaluate whether our products' sound insulation is sufficient to meet your needs.</p>		
DoP	Available		
LEED	TVOC	approved emissions (EN ISO 16000-9)	

Formaldehyde	approved emissions (EN 717-1) No added urea formaldehyde
Recycled Material	Wall materials in 17% Post Consumer
Certified Wood	FSC available, Certificate Code: SCS-COC-005137
EPD	available
Production Site	city: Gustafs / country: Sweden
Life time	expected > 50 years

BREEAM

TVOC	approved emissions (EN ISO 16000-9)
Formaldehyde	approved emissions (EN 717-1) No added urea formaldehyde
Recycled Material	Wall materials in 17% Post Consumer
Certified Wood	FSC available, Certificate Code: SCS-COC-005137
EPD	available
Production Site	city: Gustafs / country: Sweden
Life time	expected > 50 years

TABLES

Wall suspended table Medium Single working for 1 person, 400x700 mm, facing the side wall(s).
Adjustable height: 760 mm for chair or 1020 mm for standing or bar stool, the table can be used on both the left or right wall.
Table top surface: Ash / Oak / Cherry / Walnut / White CPL / Black CPL
Table support: Black

Wall suspended table Wide Single working for 1 person, 400x700 mm, facing the side wall(s).
Adjustable height: 760 mm for chair or 1020 mm for standing or bar stool, the table can be used on both the left or right wall.
Table top surface: Ash / Oak / Cherry / Walnut / White CPL / Black CPL
Table support: Black

Wall suspended table Facing the back glass Single working for 1 person 450x990 mm, facing the back glass.
Adjustable height: 760 mm for chair or 1020 mm for standing or bar stool.
Table top surface: Ash / Oak / Cherry / Walnut / White CPL / Black CPL
Table support: Black

SPECIFICATION TEXT

ST-Gpod Mini Linear / Mobile, Silent and Private Work Space

BAR STOOL

Bar stool

Black coated steel construction with ergonomic leather seat in diameter 380 mm. Turnable 360°
Sit height free adjustable from 600 to 800 mm.
Foot rest included.

Total depth: 450 mm
Total width: 380 mm
Weight: 8,9 kg