

129323RE - Single Sided PE Protection Tape

Description	A strong and conformable red Polyethylene film tape coated on one side with a high tack solvent based acrylic adhesive.
Product properties	The tape has excellent UV-light resistance and resistance to ageing, moisture, abrasion and weathering. It has good adhesion on both even and rough and uneven surfaces.
Applications	It is primarily used as a masking tape for stucco application but may also be used as a weather seal for applying plastic storm windows, film can sealing, ink container sealing, and poly sheeting where adhesive removability is desired. Also for surface protection of glazed and printed surfaces. Used in all applications where there is a need for excellent longterm protection on smooth and rough substrates in building, automotive and aerospace industries.
Storage and ageing	1 year shelf life whilst stored in original packaging and ambient room temperature. Keep out of direct sunlight.
Applying tips	All substrates should be clean and contamination free, a solvent such as Isopropyl-Alcohol is recommended for cleaning purposes, and the tape should be applied with pressure.

TECHNICAL DATA

Weather resistant	Yes	
UV resistant	Yes	
Aging resistant	Yes	
Plasticizer resistant	Yes	
Color	Red	
Thickness carrier	0.1 mm	3.937 Mils
Thickness total	0.13 mm	5.118 Mils
Adhesion on SS	7 N/25mm	1.6 Lbs/inch
Tensile strength length	45 N/25mm	10.28 Lbs/inch
Elongation length	500 %	
Service temperature	Between -40 and 80 °C	Between -40 and 176 °F

Disclaimer: Values shown in this document are averages only. For legal reasons, we emphasize that the information on this data is available "as is" and that Stokvis Tapes, an ITW company, gives no guarantees with respect to the accuracy and completeness nor with respect to interpretations made on the basis of this information. See our applicable delivery conditions. Each user should conduct his own tests to determine the suitability of the product for his intended use and shall assume all risks and liability in connection therewith. Stokvis Tapes cannot be held liable for any damages resulting from the unsuitability of the product. Many factors beyond the control of Stokvis Tapes may affect the use and performance of the product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluates the Stokvis Tapes product to determine whether it is fit for a particular purpose and suitable for the user's method of application. The information is available to the user for viewing, copying and distributing, provided that Stokvis Tapes, an ITW company, is always quoted as the source. The information is intended solely for informational and non-commercial use. Intellectual property: Stokvis Tapes, an ITW company, reserves all rights regarding this document and the information contained herein. Reproduction, use or disclosure to third parties without express permission is strictly forbidden.